



SWD Quik-Shield® | 1000 Roof Primer

SWD Quik-Shield® | 1000 is an excellent primer-sealer that ensures maximum adhesion between the roofing substrate and SWD Quik-Shield® | 125 roofing foam.

SWD Quik-Shield® | 1000 is an integral part of any foam roofing system because it has been specifically designed to improve adhesion of rigid polyurethane foam to almost any roofing substrate including:

- Asphalt
- Modified
- BUR
- Smooth Surfaced
- Metal
- Single Ply
- Concrete

SWD Quik-Shield® | 1000 is also designed for use on acrylic coated roofing to prepare for re-coatings. It is ideal for use with existing spray polyurethane foam roofing to prepare for re-coating or transition from traditional roof coatings to an acrylic based coatings.



SWD Quik-Shield® | 1000 **Part of an ideal roofing solution**

Today's ideal roofing systems provide more than ever. A top quality foam roofing system delivers:

- High insulation value
- Increased structural stability
- Optimum air-barrier performance

The foundation for any foam roofing solution is the primer coating. SWD Quik-Shield® | 1000 is the ideal product for start a roofing system. Applied directly to the roof deck, the primer ensures maximum adhesion of the roof foam. An ideal roofing solution is topped off with a high reflectivity coating.

SWD offers complete roofing system solutions that have proven results. From primer to foam to coating, each component is specifically designed work together.



SWD Quik-Shield® | 1000

Roof Primer - Specifications

APPLICATION:

SWD Quik-Shield® | 1000 is designed to be sprayed through airless spray equipment. It may also be applied with a brush or roller.
All surfaces should be clean and free from all moisture, oil, grease, loose particles, dust, debris, and any other materials that would prevent maximum adhesion.
Under normal clear weather conditions spray foam may be applied after 2 hours cure.
Cure time will be faster at higher ambient temperatures.

STORAGE:

For maximum shelf life, store materials in a cool dry area
Keep container tightly sealed.
Storage temperatures of 60-80°F are recommended.
Lower storage temperatures will cause temporary increase in viscosity.
Rotate stock on a "First-In First Out" basis.

PRECAUTIONARY AND SAFETY MEASURES:

WARNING: FLAMMABLE-SWD-1000 liquid is extremely flammable.
Keep away from heat, sparks, and open flame.
Do not smoke around material.
Solvents are present, ensure adequate ventilation .
Turn off all non-explosion proof electrical equipment and other sources of ignition while spraying.
Keep container closed when not in use.
Avoid contact with skin or eyes; may cause irritation.
In case of contact, immediately flush with plenty of water for at least 15 minutes and get medical attention.
Do not take internally.

PROPERTIES:

TYPE:	Neoprene
WEIGHT/ GALLON:	6.6 lbs.
FLASH POINT	less than 0°F
VISCOSITY:	200 cps
SHELF LIFE:	6 months at 75°F
SOLIDS:	10%

APPROXIMATE COVERAGE:

Wood	200 sq.ft. /gallon
Metal	200 sq.ft. /gallon

This information herein is believed to be reliable, however, unknown risks may be present. SWD Urethane Company makes no warranty, expressed or implied, concerning this product's merchantability or fitness for any particular use. The only warranty SWD Urethane Company give is that the product meets the specifications herein listed, and in the event that it does not, that SWD Urethane Company will replace, at its costs SWD Urethane Company's product. The foregoing constitutes SWD Urethane Company's sole obligation with respect to damages, whether direct, incidental or consequential, resulting from the use or performance of the product.