



# Venture Tape

30 Commerce Road  
Rockland, MA 02370-0384

9/23/2008

781-871-1400  
Fax: 781-871-0065

## 1718

### **1/8" VINYL FOAM SEALANT TAPE**

**DESCRIPTION:** A specially formulated pressure sensitive adhesive system applied to a very flexible, closed cell vinyl foam. The vinyl foam tape gray in color and has a density of 6 to 9 lb. per cubic foot.

**APPLICATION:** Used as a vapor seal where large spaces occur, and as a lap joint seal in corrugated metal building panels or prefabricated wall panels.

#### TECHNICAL DATA

	<u>IMPERIAL</u>	<u>METRIC</u>
<b>Thickness (exclusive of liner):</b>	1/8" (0.125")	3.175 mm
<b>Adhesion (PSTC #1):</b>	20 oz./in.width	5.7 N/2.5 cm
<b>Tensile:</b>	35 psi	158.5 N/2.5 cm
<b>Elongation:</b>	130 %	130 %
<b>Force To Compress (ASTM D1667):</b>	3.5+/- 1 psi	15.9+/-4.5 N/2.5 cm
<b>Compression Deflection (ASTM D1667):</b>	2.5+/- 1 psi	11.3+/-4.5 N/2.5 cm
<b>Compression Set @ 25% (ASTM D1667):</b>	15 % max.	15 % max.
<b>Shore 00 Durometer (ASTM D2240):</b>	35 +/- 5	
<b>Temperature Resistance:</b>	-20 F to 130 F	29.9 C to 54.4 C

**IMPORTANT INFORMATION:**

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities. 5/12/00